



SPECIFICATIONS FOR ROTATOR

| | |
|---------------------------|-------------------------------------|
| MODEL | CR-60 |
| SAFE WORKING LOAD | 30 METRIC TONNES |
| VESSEL SIZE MINIMUM | Ø570mm @ 80° INCLUDED ANGLE |
| VESSEL SIZE MAXIMUM | Ø6800mm @ 50° INCLUDED ANGLE |
| WHEEL CENTRE DISTANCE C-C | 700,1100,1500,1900,2300,2700,3100mm |
| TYRE/DRUM TYPE & SIZE | Ø20½" x 14" POLYURETHANE TYRES |
| COLOUR | RAL3003 RED |
| WEIGHT | 1250 kg |

NOTE:
 1/ THIS DRAWING WAS ACCURATE AT TIME OF PREPARATION BUT IS SUBJECT TO FINAL DESIGN REVISIONS

| | | | | | |
|--------------------|------------------------------|---|-----------|--------------------------------|----------|
| | | TITLE: IDLER UNIT OVERVIEW FOR CR-60 TON | | DRAWING NUMBER CR-60-1-1002 | REV 5 |
| A3 DO NOT SCALE | THIRD ANGLE PROJECTION | | DRAWN BY: | SCALE 1:20 | |
| | | | DATE: | | |