

The Swift-Cut Pro Range

A collection of four cutting edge CNC plasma cutting tables. With it's easy to use software, the Swift-Cut Pro range promises high speed precision cutting at a low cost investment. Easy to use, simple to learn and operate with exceptional aftercare and support, the Swift-Cut Pro range is the answer to affordable in-house metal cutting.

Fully enclosed cutting head

Fully enclosed cutting head offers protection to key components against the harsh cutting environment.

Automatic height control

Automatic torch height control maintains the correct cutting height resulting in improved cut quality and consumable life.

Plate sensor

Pneumatically driven "Soft Sense" soft touch plate sensor accurately locates the plate surface even on thin materials.

Gantry beam

Lightweight but rigid gantry beam supports twin x-axis linear rails, it also gives you the ability to cut 100mm box sections.

Heavy duty gantry

Heavy duty gantry end castings with machined faces provide a precise and stable platform for the cutting head.

Enclosed drag chains

Fully enclosed drag chains protect cables against damage from molten material.

Linear rail

Precision linear rail on all axes combined with hybrid servo motor encoder feedback delivers exceptional positioning accuracy.

Engraving tool

The Swift-Cut engraving tool allows you to mark and cut in one operation, meaning no more outsourcing or moving your project from one machine to another (optional extra).

Laser aid

Laser cross hairs aid in the positioning of the cutting head.

Water table bed

The water table bed option offers efficient fume suppression so that no external fume extraction is required.
Alternatively, the zoned downdraft table option (only available in the 3000m machine size) captures fumes and particles from beneath the cutting area.

Operators console

Software


Swift-Cut's easy to use

one-piece software

Ergonomic operators console with touch screen and keyboard/mouse inputs.

Heavy duty base

Heavy duty base redesigned from the ground up provides support and rigidity.




The Swift-Cut Pro range comes with advanced industry leading features as standard, combined with easy to use and intuitive software. The Pro range is designed to take metal cutting to another level - its incredible capabilities offer exceptional high-end cutting solutions at amazingly low prices.



SwiftCAM

Swift-Cut's easy to use software guarantees that anyone with a basic knowledge of computers will be capable of operating the CNC plasma cutting system. Minimal training means the table will be operational almost immediately, maximising output from the start.



Automatic control

Serial link with Hypertherm Powermax – Automatic control of plasma settings.

Easy to use with basic and advanced screens.

Sheet Alignment

Align the cutting path with misaligned sheets on the cutting bed.

Sheet Trim

Easily trim scrap material from sheet stock.

Easily recover interrupted cuts due to a breakaway head or emergency stop condition.

G-Code Favourites

Save up to 5 g-code files for quick loading.

Run the g-code file without cutting.

Automatic lead in/out

Software automatically applies lead ins/out for quicker programming.

JPEG/DXF/DWG import capable

Import .dxf files or convert .jpg images for cutting.

Automatically nests parts for economical sheet usage.

Nest parts in scrap areas to fully utilise the sheet.

Customisable cutting rules

Optimise cutting parameters for best cutting performance.

Customisable toolsets

Modify or create toolsets for new materials.

3D Cut Simulation*

Play a 3D machine simulation of the cutting operation.

Preview the part in 3D before cutting.

Parametric shape library

Over 80 configurable shapes.

5 user configurable reference points for jig fixtures.

G-Code Queue

Queue up to 5 g-code files for quick loading.



Available in 4 sizes



Pro 1250

1250mm x 1250mm

cutting area (4' x 4')



Pro 2500

2500mm x 1250mm

cutting area (8' x 4')





Pro 3000

3000mm x 1500mm

cutting area (10' x 5')



Pro 4000

4000mm x 2000mm cutting area (13' x 6.5')

Due for release early 2019

Cutting Power Options

Plasma Source: Hypertherm

| Max pierce capacity | Mild steel | Stainless steel | Aluminium | Duty cycle | 100% duty cycle |
|---------------------|------------|-----------------|-----------|------------|-----------------|
| Powermax 45* | 12mm | 12mm | 10mm | 50% | 32Amps |
| Powermax 65 | 16mm | 12mm | 12mm | 50% | 46 Amps |
| Powermax 85 | 19mm | 16mm | 16mm | 60% | 66 Amps |
| Powermax 105 | 22mm | 20mm low use | 20mm | 80% | 94 Amps |
| Powermax 125 | 25mm | 20mm | 25mm | 100% | 125 Amps |
| MAX PRO 200** | 30mm | 25mm | 25mm | 100% | 200 Amps |

^{*} Single phase ** Only available with Pro 4000



For more information contact swift-cut.com



